Product Comparison



through paper path for special

Product Name	<u>HP LaserJet Enterprise P3015n</u> Printer (CE527A)	HP LaserJet Enterprise P3015dn Printer (CE528A)	<u>HP LaserJet Enterprise P3015x</u> <u>Printer (CE529A)</u>
PRINTER Brint Technology	Laser	Laser	Laser
Print Technology Print Speed Black, Letter:	Lasei	Lasei	Lasei
ISO/Best Quality	Up to 42 ppm ¹	Up to 42 ppm ¹	Up to 42 ppm ¹
First Page Out			eAs fast as 7.5 sec from Ready mode
Processor	540 MHz	540 MHz	540 MHz
Paper Trays, Std	2	2	3
Paper Trays, Max	4	4	4
Input Capacity, Std	600 sheets	600 sheets	1,100 sheets
Input Capacity, Max	1,600 sheets	1,600 sheets	1,600 sheets
Output Capacity, Std	250 sheets	250 sheets	250 sheets
Output Capacity, Max	250 sheets	250 sheets	250 sheets
Envelope Input, Std	10	10	10
Envelope Feeder	No	No	No
Two-Sided Printing	Manual	Automatic (standard)	Automatic (standard)
Typefaces		PCL: 103 internal font set (plus Greek, Hebrew, Cyrillic, Arabic); PS: 93 internal font set (plus Greek, Hebrew, Cyrillic, Arabic). Additional Font Solutions available at http:// www.hp.com/go/laserjetfonts	PCL: 103 internal font set (plus Greek, Hebrew, Cyrillic, Arabic); PS: 93 internal font set (plus Greek, Hebrew, Cyrillic, Arabic). Additional Font Solutions available at http:// www.hp.com/go/laserjetfonts
Prints Color	No	No	No
Print Quality, Black Best	Up to 1200 x 1200 dpi	Up to 1200 x 1200 dpi	Up to 1200 x 1200 dpi
Print Resolution Technology	HP ProRes 1200	HP ProRes 1200	300 dpi, 600 dpi, HP FastRes 1200, HP ProRes 1200
Print Languages, Std	HP PCL 6, HP PCL 5e, HP postscript level 3 emulation	HP PCL 6, HP PCL 5e, HP postscript level 3 emulation	HP PCL 6, HP PCL 5e, HP postscript level 3 emulation
Printer Management	HP Web Jetadmin, HP LaserJet Utility, HP Embedded Web Server, Easy Printer Care	HP Web Jetadmin, HP LaserJet Utility, HP Embedded Web Server, Easy Printer Care	HP Web Jetadmin, HP LaserJet Utility, HP Embedded Web Server, Easy Printer Care
Display Type GENERAL	2.25-in, 4-line LCD (text)	2.25-in, 4-line LCD (text)	2.25-in, 4-line LCD (text)
Duty Cycle, Monthly	Up to 100,000 pages	Up to 100,000 pages	Up to 100,000 pages
Recommended Monthly Volume		1,500 to 5,000 pages	1,500 to 5,000 pages
Media Types	Paper (bond, color, letterhead, plain, preprinted, pre-punched, recycled, rough), envelopes, labels, cardstock, transparencies, user- defined	Paper (bond, color, letterhead, plain, preprinted, pre-punched, recycled, rough), envelopes, labels, cardstock, transparencies, user- defined	Paper (bond, color, letterhead, plain, preprinted, pre-punched, recycled, rough), envelopes, labels, cardstock, transparencies, user- defined
Media Sizes, Std	Letter, legal, 8.5 x 13 in, executive,	Letter, legal, 8.5 x 13 in, executive,	Letter, legal, 8.5 x 13 in, executive,

Media Sizes, Std Letter, legal, 8.5 x 13 in, executive, Letter, legal, 8.5 x 13 in, executive, Letter, legal, 8.5 x 13 in, executive, envelopes envelopes envelopes Media Sizes, Std, Metric A4, A5, B5 (JIS), A6 A4, A5, B5 (JIS), A6 A4, A5, B5 (JIS), A6 Media Sizes, Custom Tray 1: 3 x 5 in to 8.5 x 14 in; tray 2 Tray 1: 3 x 5 in to 8.5 x 14 in; tray 2 Tray 1: 3 x 5 in to 8.5 x 14 in; trays and optional trays 3, 4: 4.1 x 5.8 in and optional trays 3, 4: 4.1 x 5.8 in 2, 3 and optional tray 4: 4.1 x 5.8 in to 8.5 x 14 in to 8.5 x 14 in to 8.5 x 14 in Tray 1: 76 x 127 to 216 x 356 mm; Tray 1: 76 x 127 to 216 x 356 mm; Tray 1: 76 x 127 to 216 x 356 mm; Media Sizes, Custom, Metric tray 2 and optional trays 3, 4: 105 x tray 2 and optional trays 3, 4: 105 x trays 2, 3 and optional tray 4: 105 x 148 to 216 x 356 mm 148 to 216 x 356 mm 148 to 216 x 356 mm Tray 1: 16 to 53 lb (straight-through Tray 1: 16 to 53 lb (straight-through Tray 1: 16 to 53 lb (straight-through **Media Weights** paper path for special media and paper path for special media and paper path for special media and heavier stock); trays 2, 3 and heavier stock); tray 2 and optional heavier stock); tray 2 and optional optional tray 4: 16 to 32 lb trays 3, 4: 16 to 32 lb trays 3, 4: 16 to 32 lb Media Weights, Metric Tray 1: 60 to 199 g/m² (straight Tray 1: 60 to 199 g/m² (straight Tray 1: 60 to 199 g/m² (straight

through paper path for special

through paper path for special

	media); tray 2 and optional trays 3, 4: 60 to 120 g/m ²	media); tray 2 and optional trays 3, 4: 60 to 120 g/m ²	media); trays 2, 3 and optional tray 4: 60 to 120 g/m ²
Connectivity, Std	HP Jetdirect 10/100/1000T Etherner embedded print server, 1 external Host USB, 2 internal accessory ports for HP and partner solutions	t HP Jetdirect 10/100/1000T Etherne embedded print server, 1 external Host USB, 2 internal accessory ports for HP and partner solutions	Hi-Speed USB 2.0, 1 open EIO slot, t HP Jetdirect 10/100/1000T Ethernet embedded print server, 1 external Host USB, 2 internal accessory ports for HP and partner solutions
Connectivity, Opt	HP Jetdirect internal, external and wireless print servers	HP Jetdirect internal, external and wireless print servers	HP Jetdirect internal, external and wireless print servers
Mobile Printing Capability	None	None	None
Memory, Std	128 MB	128 MB	128 MB
Memory, Max	640 MB	640 MB	640 MB
Hard Disk Drive	Optional, HP High-Performance Secure EIO Hard Disk (EIO Hard Drive)	Optional, HP High-Performance Secure EIO Hard Disk (EIO Hard Drive)	Optional, HP High-Performance Secure EIO Hard Disk (EIO Hard Drive)
Power Supply Type	Internal power supply	Internal power supply	Internal power supply
Power Supply Required	110-volt input voltage: 100 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz)	220-volt input voltage: 220 to 240	110-volt input voltage: 100 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz)
Power Consumption	780 watts (Printing), 14.5 watts (Ready), 8.5 watts (Sleep), 0.6 watts (Off) ²	780 watts (Printing), 14.5 watts (Ready), 8.5 watts (Sleep), 0.6 watts (Off) ²	780 watts (Printing), 14.5 watts (Ready), 8.5 watts (Sleep), 0.6 watts (Off) ²
Typical Electricity Consumption (TEC)	3.267 kWh/Week	3.267 kWh/Week	3.267 kWh/Week
ENERGY STAR® Qualified	No	Yes	Yes
Mac Compatible	Yes	Yes	Yes
Dimensions (W x D x H)	17.6 x 28.7 x 12.4 in (maximum), 17.6 x 16.2 x 12.4 in (minimum)	17.6 x 28.7 x 12.4 in (maximum), 17.6 x 16.2 x 12.4 in (minimum)	17.6 x 28.7 x 18.9 in (maximum), 17.6 x 16.2 x 18.9 in (minimum)
Weight	35 lb	35 lb	46.6 lb
Dimensions, Metric	448 x 730 x 316 mm (maximum), 448 x 412 x 316 mm (minimum)	448 x 730 x 316 mm (maximum), 448 x 412 x 316 mm (minimum)	448 x 730 x 480 mm (maximum), 448 x 412 x 480 mm (minimum)
Weight, Metric	15.9 kg	15.9 kg	21.2 kg
Shipping Dimensions	23.6 x 19.7 x 17.3 in	23.6 x 19.7 x 17.3 in	23.6 x 19.7 x 26.6 in
Shipping Weight	43.7 lb	43.7 lb	57.4 lb
Shipping Dimensions, Metric	600 x 500 x 439 mm	600 x 500 x 439 mm	600 x 500 x 676 mm
Shipping Weight, Metric	19.9 kg	19.9 kg	26.1 kg
Pallet Dimensions	47 x 39 x 91 in	47 x 39 x 91 in	47 x 39 x 80 in
Pallet Dimensions, Metric	1200 x 1000 x 2309 mm	1200 x 1000 x 2309 mm	1200 x 1000 x 2297 mm
Pallet Weight	926 lb	926 lb	739 lb
Dellet Material Materia	101 kg	421 kg	000 1
Pallet Weight, Metric Quantity Per Pallet	421 kg 20	421 kg 20	336 kg 12

The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

- 1. Measured using ISO/IEC 24734, excludes first set of test documents. For more information see http://www.hp.com/go/ printerclaims. Exact speed varies depending on the system configuration, software application, driver and document complexity.
- 2. Values subject to change. Power numbers are the highest values measured using all standard voltages. See http:// www.hp.com/support for current information.